

Analogue Multi-Heat Sensor

ACB-E



Features

- ▶ User selectable modes
- ▶ Incorporates Fixed Temperature and Rate Of Rise Heat elements
- ▶ Twin fire LED's allow 360° viewing
- ▶ Pulsing/non-pulsing controlled from panel
- ▶ Electronically Addressed
- ▶ LPCB approved to Classes A, B & C

Description

Model ACB-E is a Multi-Heat Sensor, which is fully compatible with Hochiki's ESP Analogue Addressable Protocol.

The ACB-E incorporates a Variable Temperature heat element and a Rate Of Rise heat element, both of which are controlled from the Control Panel, allowing either thermal element or both elements simultaneously to be active in making the fire decision. The sensor polling LED's can also be controlled via the Control Panel (pulsing/non-pulsing).

| Specification | |
|-----------------------------------|-------------------------------------|
| Ordering Code | ACB-E ACB-E(WHT) |
| Operating Voltage | 17 - 41Vd.c. |
| Low Power Mode (typ) | 110µA |
| Quiescent Current (typ) | 350µA |
| Alarm Current (controlled by CIE) | 19mA |
| Transmission Method | Digital Communications Using ESP |
| Operating Temperature Range | -10°C to +50°C |
| Storage Temperature Range | -30°C to +70°C |
| Maximum Humidity | 95%RH - Non Condensing (at 40°C) |
| Ingress Protection Rating | IP64 |
| Colour / Case Material | Ivory or White / Polycarbonate |
| Weight (g) | 100 |
| Diameter (mm) / Height (mm) | 100 / 38 |
| Compatible Bases | YBN-R/3, YBO-BS, YBO-BSB, YBO-R/SCI |
| Base Fixing Centres (mm) | 48 ~ 74 |